



AVENO FS WIV-Combi 5W-30

AVENO FS WIV-Combi 5W-30 is a synthetic, extremely efficient engine oil for modern petrol and diesel engines with or without turbocharging and direct injection. AVENO FS WIV-Combi 5W-30 is characterized by the minimization of fuel consumption, excellent oil supply during cold start and provides a high level of wear and corrosion prevention. Guarantees extended drain intervals in accordance with manufacturer's instructions.

Instructions for use

AVENO FS WIV-Combi 5W-30 is an energy-saving engine oil for year-round use and ideal for all modern petrol and diesel engines. AVENO FS WIV-Combi 5W-30 extends the life of the particulate filter. Follow the vehicle and engine manufacturer's operating instructions.

Quality classification

Specification

- API SN
- ACEA C3

Recommendation

- BMW Longlife-04
- Fiat 9.55535-S3
- MB 229.31, MB 229.51
- Porsche C30
- VW 504 00/507 00

Properties

- Excellent cold start properties.
- High shear stability.
- Neutrality towards sealants.
- Suitable for catalysts.
- Very stable and excellent viscosity retention, even at high speeds.
- Save fuel in any operating mode.

- Low evaporation and therefore low oil consumption.
- Extended drain intervals conserve natural resources.

Technical Specifications

Property	Value	Unit	Testing method
Kinematic viscosity at 40°C	73.2	mm²/s	DIN 51659-02:2017-02
Kinematic viscosity at 100°C	12.2	mm²/s	DIN 51659-02:2017-02
Viscosity index	164		ISO 2909:2004-08
Appearance	YELLOW-BROWN		VISUAL
CCS viscosity at -30°C	5700	mpa*s	ASTM D 5293:2020
Density at 15°C	849	kg/m³	DIN EN ISO 12185:1997-11
Pour point	-39	°C	ASTM D 7346:2015
Total Base Number (TBN)	6.6	Mg koh/g	ASTM D 2896:2015